

Technical Data Sheet

ENVIRO WC315SA

Solvent Self Adhesive Wall Covering Fabric

Application

Mural, Wall Covering Frame, Exhibition, Display Systems

Technical Specifications

Substrate	210±15gsm	GB/T 451.3-2002
Material	100% Polyester	DIN 60001, ASTM D7641
Glue	Water Base Removable Clear Adhesive	---
Liner	105gsm /DSPE	GB/T 451.2-2002
Total Weight	355±20gsm	ISO536
Total Thickness	350±40µm	ISO534
Opacity	≥90%	GB/T 9754-2007
Whiteness	130±10	ISO11475
Color	L*:93±2.0; a*: 5.5±2.0; b*: -11±2.0	GB/T 7974-2002
Peel Strength [lbf/in] 15min [lbf/in]	0.5-1.5	FTM1-FINAT
Peel Strength [lbf/in] 24hrs [lbf/in]	0.8-1.8	FTM1-FINAT
Gloss [60°]	2-4	GB/T 9754-2007
Shelf Time	1 year, unopened in original packaging	---

Size

Width	1.6/2.5/2.6/3.2m	Standard	DIN EN ISO 3759, ASTM D751-2006
Length	70m	Standard	DIN EN ISO 3759, ASTM D751-2006

Storage Instructions

The product should be stored in the original packaging for protection.

It is recommended to keep it sealed and placed horizontally to avoid direct sunlight and direct contact with heat sources. Recommended storage temperature and humidity: 15°C [59°F] ~ 35°C [95°F], 20 ~ 65% RH; Under this condition, the product shelf life is 1 year.

Features



Compatible Inks

